

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

Listing of Claims:

1. (Currently Amended) A total internal reflection
fluorescence microscope comprising:

at least one objective lens which takes light from a
specimen;

5 an image pick-up device which picks up an image of the light
taken into the objective lens;

an observation optical path via which the light taken into
the objective lens is condensed onto the image pick-up device;

10 a condenser lens, which is disposed in a position facing the
objective lens via the specimen, which has a numerical aperture
that makes possible total internal reflection illumination, and
which guides a transmitted illuminative light, which is emitted
by a light source, into the specimen;

15 a base including an upper portion that holds the condenser
lens;

a laser oscillation unit which outputs a laser beam;

an optical fiber which transmits the laser beam output from
the laser oscillation unit;

20 a reflection mirror provided at a lower portion of the base
to introduce the laser beam output from the optical fiber into a
vicinity of an outermost portion of the condenser lens; ~~and~~

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

25 a condensing lens which condenses the laser beam output from
the optical fiber, such that the laser beam is condensed at a
condensing position in a vicinity of a front focal position of
the condenser lens; and

a mirror moving section which moves the reflection mirror in
a translatory manner in a direction that is substantially
perpendicular to a light path of the transmitted illuminative
light from the light source.

Claims 2 and 3 (Canceled).

4. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 1, further comprising a conversion
lens unit which converts a numerical aperture of the laser beam
incident upon the condensing position without changing the
5 condensing position of the laser beam.

5. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 4, wherein the conversion lens unit
is removably inserted between an emission end of the optical
fiber and the condensing lens.

6. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 4, wherein the conversion lens unit

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

includes a lens group which converts a numerical aperture of the laser beam incident upon the condensing position.

7. (Withdrawn) The total internal reflection fluorescence microscope according to claim 4, wherein the conversion lens unit comprises:

5 a convex lens which converts the numerical aperture of the laser beam diverged and emitted from an emission end of the optical fiber; and

a concave lens which diverges the laser beam having the numerical aperture converted by the convex lens.

8. (Withdrawn) The total internal reflection fluorescence microscope according to claim 7, wherein the concave lens is movable in an optical path direction of the laser beam between the convex lens and the condensing lens.

9. (Withdrawn) The total internal reflection fluorescence microscope according to claim 5, wherein the at least one objective lens comprises a plurality of objective lenses having different observation magnifications, and the microscope further
5 comprises:

an objective lens switching section which selectively disposes one of the plurality of objective lenses on the

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

observation optical path; and

10 a control section which controls inserting and removing of
the conversion lens unit between the emission end of the optical
fiber and the condensing lens in accordance with the observation
magnification of the objective lens disposed on the observation
optical path.

10. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 9, wherein the plurality of
objective lenses include at least one objective lens for
high-magnification observation and at least one objective
5 lens for low-magnification observation, and

wherein the control section inserts ~~the conversion lens unit~~
between the emission end of the optical fiber and the condensing
lens when the objective lens for high-magnification observation
is disposed on the observation optical path, and the control
10 section removes the conversion lens unit from between the
emission end of the optical fiber and the condensing lens
when the objective lens for low-magnification observation is
disposed on the observation optical path.

11. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 10, wherein an irradiation range of
the laser beam with respect to the specimen is caused to agree

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

with an observation range of the objective lens for
5 high-magnification observation when the conversion lens unit is
inserted between the emission end of the optical fiber and the
condensing lens, and the irradiation range of the laser beam with
respect to the specimen is caused to agree with an observation
range of the objective lens for low-magnification observation
10 when the conversion lens unit is removed from between the
emission end of the optical fiber and the condensing lens.

12. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 1, further comprising a zoom lens
unit which adjusts the condensing position of the laser beam in
the vicinity of the front focal position of the condenser lens.

13. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 12, wherein the zoom lens unit
comprises a lens group which adjusts the condensing position of
the laser beam in the vicinity of the front focal position of the
condenser lens.

14. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 12, wherein the zoom lens unit
comprises:

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

5 a convex lens which converts the numerical aperture of the
laser beam diverged and emitted from an emission end of the
optical fiber; and

a concave lens which diverges the laser beam having the
numerical aperture converted by the convex lens.

15. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 14, wherein the convex lens is
movable in an optical path direction of the laser beam between
the emission end of the optical fiber and the condensing lens.

16. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 14, wherein the concave lens is
movable in an optical path direction of the laser beam between
the convex lens and the condensing lens.

17. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 14, further comprising:

5 a control section which determines a moving position of the
concave lens to adjust the condensing position of the laser beam
in the vicinity of the front focal position of the condenser lens
in accordance with positional movement of the convex lens, and
which controls movement of the convex lens and the concave lens

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

based on information of the determined moving position of the
concave lens.

18. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 13, wherein the at least one
objective lens comprises a plurality of objective lenses having
different observation magnifications, and the microscope further
5 comprises:

an objective lens switching section which selectively
disposes one of the plurality of objective lenses on the
observation optical path; and

10 a control section which determines a relative positional
relation of the lens group disposed in the zoom lens unit in each
optical axis direction in accordance with an observation
magnification of the objective lens disposed on the observation
optical path.

19. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 18, wherein the lens group of
the zoom lens unit comprises:

5 a convex lens which converts the numerical aperture of
the laser beam diverged and emitted from an emission end of the
optical fiber; and

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

a concave lens which diverges the laser beam having the numerical aperture converted by the convex lens, and

10 wherein the control section determines a moving position of the concave lens to adjust the condensing position of the laser beam in the vicinity of the front focal position of the condenser lens in accordance with positional movement of the convex lens, and the control section controls movement of the convex lens and the concave lens based on information of the determined moving
15 position of the concave lens.

20. (Withdrawn - Currently Amended) The total internal reflection fluorescence microscope according to claim 1, wherein the laser oscillation unit, the optical fiber, the reflection mirror, the mirror moving section, and the condensing lens form a
5 laser introduction section, and the microscope comprises a plurality of said laser introduction sections, each of which emits a laser beam that is condensed at a corresponding condensing position in a vicinity of corresponding front focal positions of the condenser lens; and

10 wherein the microscope further comprises:

at least one additional image pick-up device which picks up an image of the light taken into the objective lens;

at least one additional observation optical path via which the light taken into the objective lens is condensed onto the

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

15 additional image pick-up device;

an optical dividing system which divides the light taken into the objective lens onto respective ones of the optical paths toward the image pick-up devices depending on optical characteristics of the light.

Claims 21 and 22 (Canceled).

23. (Withdrawn) The total internal reflection fluorescence microscope according to claim 21, wherein each of the plurality of laser introduction sections comprises a conversion lens unit which converts a numerical aperture of the laser beam incident upon the condensing position without changing the condensing position of the laser beam.

24. (Withdrawn) The total internal reflection fluorescence microscope according to claim 23, each said conversion lens unit is removably inserted between an emission end of the optical fiber and the condensing lens in the corresponding one of the laser introduction sections.

25. (Withdrawn) The total internal reflection fluorescence microscope according to claim 23, wherein the each said conversion lens unit includes a lens group which converts a

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

numerical aperture of the laser beam incident upon the
5 corresponding condensing position.

26. (Withdrawn) The total internal reflection fluorescence microscope according to claim 23, each said conversion lens unit comprises:

a convex lens which converts the numerical aperture of the
5 laser beam diverged and emitted from an emission end of the optical fiber in the corresponding one of the laser introduction sections; and

a concave lens which diverges the laser beam having the numerical aperture converted by the convex lens.

27. (Withdrawn) The total internal reflection fluorescence microscope according to claim 26, wherein each said concave lens is movable in an optical path direction of the laser beam between the convex lens and the condensing lens in the corresponding one
5 of the laser introduction sections.

28. (Withdrawn) The total internal reflection fluorescence microscope according to claim 24, wherein the at least one objective lens comprises a plurality of objective lenses having different observation magnifications, and the microscope further
5 comprises:

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

an objective lens switching section which selectively
disposes one of the plurality of objective lenses to take the
light from the specimen; and

10 a control section which controls inserting and removing of
the conversion lens unit in each of the plurality of laser
introduction sections between the emission end of the optical
fiber and the condensing lens in accordance with the observation
magnification of the objective lens disposed to take the light
from the sample.

29. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 28, wherein a plurality of
objective lenses include at least one objective lens for
high-magnification observation and at least one objective
5 lens for low-magnification observation, and

wherein the control section inserts the conversion lens unit
in each of the plurality of laser introduction sections between
the emission end of the optical fiber and the condensing lens
when the objective lens for high-magnification observation is
10 disposed to take the light from the sample, and removes the
conversion lens unit in each of the plurality of laser
introduction sections between the emission end of the optical
fiber and the condensing lens when the objective lens for

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

low-magnification observation is disposed to take the light from
15 the sample.

30. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 29, wherein, for each of the laser
introduction sections, an irradiation range of the laser beam
with respect to the specimen is caused to agree with an
5 observation range of the objective lens for high-magnification
observation when the conversion lens unit is inserted between the
emission end of the optical fiber and the condensing lens, and
the irradiation range of the laser beam with respect to the
specimen is caused to agree with an observation range of the
10 objective lens for low-magnification observation when the
conversion lens unit is inserted between the emission end of the
optical fiber and the condensing lens.

31. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 20, wherein each of the plurality
of laser introduction sections further comprises a zoom lens
unit which adjusts the condensing position of the laser beam in
5 the vicinity of the front focal position of the condenser lens.

32. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 31, wherein each said zoom lens

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

unit comprises a lens group which adjusts the condensing position
of the laser beam in the vicinity of the front focal position of
5 the condenser lens.

33. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 31, wherein the lens group of each
said zoom lens unit comprises:

a convex lens which converts the numerical aperture of the
5 laser beam diverged and emitted from an emission end of the
optical fiber in the corresponding laser introduction section;
and

a concave lens which diverges the laser beam having the
numerical aperture converted by the convex lens.

34. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 33, wherein each said convex lens
is movable in an optical path direction of the laser beam between
the emission end of the optical fiber and the condensing lens in
5 the corresponding one of the laser introduction sections.

35. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 33, wherein each said concave lens
is movable in an optical path direction of the laser beam between

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

the convex lens and the condensing lens in the corresponding one
5 of the laser introduction sections.

36. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 33, further comprising:

a control section which determines, for each said zoom lens
unit, a moving position of the concave lens to adjust the
5 condensing position of the laser beam in the vicinity of the
front focal position of the condenser lens in accordance with
positional movement of the convex lens, and which controls
movement of the convex lens and the concave lens based on
information of the determined moving position of the concave
10 lens.

37. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 32, wherein the at least one
objective lens comprises a plurality of objective lenses having
different observation magnifications, and the microscope further
5 comprises:

an objective lens switching section which selectively
disposes one of the plurality of objective lenses to take the
light from the specimen; and

a control section which determines a relative positional
10 relation of the lens groups disposed in the zoom lens units in

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

each optical axis direction in accordance with an observation magnification of the objective lens disposed on the observation optical path.

38. (Withdrawn) The total internal reflection fluorescence microscope according to claim 37, wherein the lens group of each said zoom lens unit comprises:

5 a convex lens which converts the numerical aperture of the laser beam diverged and emitted from an emission end of the optical fiber in the corresponding laser introduction section; and

a concave lens which diverges the laser beam having the numerical aperture converted by the convex lens, and

10 wherein, for each of the zoom lens units, the control section determines a moving position of the concave lens to adjust the condensing position of the laser beam in the vicinity of the front focal position of the condenser lenses in accordance with positional movement of the convex lens, and the control
15 section controls movement of the convex lens and the concave lens based on information of the determined moving position of the concave lens.

39. (Withdrawn) The total internal reflection fluorescence microscope according to claim 20, wherein the plurality of laser

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

introduction sections are disposed radially around the
transmitted illuminative light path and extend in directions that
5 are substantially perpendicular to a path of the transmitted
illuminative light.

40. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 20, further comprising:

at least one optical path length adjustment section which is
disposed on at least one divided observation optical path among
5 the plurality of divided observation optical paths divided by the
optical dividing system and which extends and contracts
an optical path length.

41. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 40, wherein the optical path length
adjustment section comprises:

a fixed prism group fixed/disposed on the divided
5 observation optical path; and

a movable prism which is movable away from and toward the
fixed prism group.

42. (Withdrawn) The total internal reflection fluorescence
microscope according to claim 40, further comprising:

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

a control section which calculates/processes an extension/contraction of the optical path length by the optical path length adjustment section.

43. (Withdrawn) The total internal reflection fluorescence microscope according to claim 20, further comprising:

a plurality of shutters disposed in the plurality of laser introduction sections; and

5 a control section which controls opening and closing of the plurality of shutters to control introducing and blocking of the laser beams from the laser introduction sections.

44. (Withdrawn) The total internal reflection fluorescence microscope according to claim 20, wherein the plurality of laser introduction sections includes at least two laser introduction sections which output laser beams a same wavelength.

45. (Currently Amended) A total internal reflection fluorescence microscope comprising:

at least one objective lens which takes light from a specimen;

5 an image pick-up device which picks up an image of the light taken into the objective lens;

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

an observation optical path via which the light taken into the objective lens is condensed onto the image pick-up device;

10 a condenser lens, which is disposed in a position facing the objective lens via the specimen, which has a numerical aperture that makes possible total internal reflection illumination, and which guides a transmitted illuminative light, which is emitted by a light source, into the specimen;

15 a base including an upper portion that holds the condenser lens;

a laser oscillation unit which outputs a laser beam; ~~and~~
a laser introduction section which comprises a reflection mirror provided at a lower portion of the base to introduce the laser beam output from the laser oscillation unit into a vicinity
20 of an outermost portion of the condenser lens; and

a mirror moving section which moves the reflection mirror in a translatory manner in a direction that is substantially perpendicular to a light path of the transmitted illuminative light from the light source.

46. (Currently Amended) A total internal reflection fluorescence microscope comprising:

at least one objective lens which takes light from a specimen;

Application No. 10/816,489
Response to Final Office Action

Customer No. 01933

5 an image pick-up device which picks up an image of the light taken into the objective lens;

an observation optical path via which the light taken into the objective lens is condensed onto the image pick-up device;

10 a condenser lens, which is disposed in a position facing the objective lens via the specimen, which has a numerical aperture that makes possible total internal reflection illumination, and which guides a transmitted illuminative light, which is emitted by a light source, into the specimen;

a laser oscillation unit which outputs a laser beam; and

15 a laser introduction section which comprises a reflection mirror provided integrally at a lower portion of the condenser lens to introduce the laser beam output from the laser oscillation unit into a vicinity of an outermost portion of the condenser lens; and

20 a mirror moving section which moves the reflection mirror in a translatory manner in a direction that is substantially perpendicular to a light path of the transmitted illuminative light from the light source.